

CROSSOVER POLICY

Document Control Statement – This Policy is maintained by Technical Services. Any printed copy may not be up to date and you are advised to check the electronic copy at on the City website to ensure that you have the current version. Alternatively, you may contact Customer Service on ~~(08)~~ 9186_8555

1. OBJECTIVE

The objective of this policy is to ensure that vehicle crossovers and rear access driveways are constructed in accordance with the City's *Vehicle Crossover Specification and Drawings* and the requirements of the *Local Government Act 1995* (the Act) and its subsidiary legislation.

2. DEFINITIONS

Road Reserve	The portion of land between the front property boundaries that contains both verges and the road carriageway.
Verge	The section of the road reserve between the property boundary and the road kerb line.
Drainage Reserve	The portion of land between the rear property boundaries that is set aside for drainage purposes usually containing either a drainage basin or an open drain.
Crossover	The portion of a driveway within the verge providing access from the road to the property boundary.
Rear Access Driveway	The portion of a driveway within the road or drainage reserve providing access to the rear property boundary.
Standard Crossover	<p>A standard residential/group dwelling crossover shall be defined as 3 metres wide, shall be constructed with concrete and exclude stormwater management elements.</p> <p>A standard commercial/industrial crossover shall be defined as 6 metres wide, shall be constructed with concrete and exclude stormwater management elements.</p>

3. PRINCIPLES

~~3.1~~ 3.1 Policy Content

Vehicle crossovers are required to be constructed prior to the occupation of a residence or clearance of conditions of a development. All crossovers and rear access driveways must be approved by the City prior to construction. The City may also request a property owner to construct a crossover or rear access driveway within a specified timeframe. A property owner may be eligible for a crossover subsidy in certain circumstances.

~~3.2~~ 3.2 Legislation

Infringements of up to \$5,000 may apply if a property owner does not comply with this Policy, the *Local Government Act 1995* and the *Local Government (Uniform Local Provisions) Regulations 1996* and in particular Regulations:—

12. Crossing from public thoroughfare to private land or private thoroughfare
13. Requirement to construct or repair crossing

- 14 Role of the Commissioner of Main Roads in some cases
- 15 Contribution to cost of crossing

3.3 4.1 General Conditions

The following general conditions apply to this Policy:

- ~~3.3.1 4.3.1~~ This policy only applies to L local G government gazetted roads.
- ~~3.3.2 4.3.2~~ Crossovers for properties that abut a State Government Road require Main Roads WA approval for crossover location, turning movement requirements, width and site distance. Construction of the crossover/drainage requirements and verge reinstatement are to be in accordance with the City's Vehicle Crossover Specification and must be approved by the City.
- ~~3.3.3 4.3.3~~ The approval of crossover construction is subject to the submission of an Application for Vehicle Crossover form and inspection processes, prior to commencing construction.
- ~~4.3.2~~ Crossovers for properties that abut a State Government Road require Main Roads WA approval for crossover location, turning movement requirements, width and site distance. Construction of the crossover/drainage requirements and verge reinstatement are to be in accordance with the City's Vehicle Crossover Specification and must be approved by the City.
- ~~4.3.3~~ The approval of crossover construction is subject to the submission of an Application for Vehicle Crossover form and inspection processes, prior to commencing construction.
- ~~3.3.4 4.3.4~~ The property owner is responsible for contacting Dial Before You Dig (1100) and other service and utility providers prior to commencing construction to ensure that underground services and infrastructure are not damaged and correct clearances are maintained.
- ~~3.3.5 4.3.5~~ Vehicle crossovers/driveways shall be constructed under the supervision and to the satisfaction of the City's officers. Contractors/owners are responsible for notifying the City prior to any preparatory or construction works to ensure that the correct inspections are conducted.
- ~~3.3.6 4.3.6~~ The contractor/owner is responsible for all traffic and pedestrian management during the crossover construction, in accordance with AS1742.3 2009 Code of Practice for Traffic Management at Road Works.
- ~~3.3.7 4.3.7~~ The contractor shall maintain public liability insurance to the value of five million dollars (\$5,000,000) during the crossover construction.
- ~~3.3.8 4.3.8~~ The contractor/owner is responsible for repairs to any damaged infrastructure occurring during the crossover construction.
- ~~3.3.9 4.3.9~~ The contractor/owner is responsible for reinstatement and clean-up of the verge immediately after completion of construction.
- ~~3.3.10 4.3.10~~ The City reserves the right to remove a crossover/rear access driveway for the purpose of carrying out works. Reinstatement of an approved crossover/rear access driveway shall be carried out by the City in consultation with the property owner.
- ~~3.3.11 4.3.11~~ The owner accepts responsibility for removal and reinstatement of crossovers/rear access driveways if required by public utility providers.
- ~~3.3.12 4.3.12~~ A crossover subsidy will only apply to the first crossover installed at the property.
- ~~3.3.13 4.3.13~~ If a rear access driveway/second crossover is required, the contractor/owner will be required to submit a Crossover Application Form and comply with all inspection processes, prior to commencing construction.
- ~~3.3.14 4.3.14~~ Redundant crossovers, due to redevelopment of a site, are to be removed. Replacement of kerb, backfilling and verge area to be reinstated at the owner's/developer's expense; and.

3.3.15 ~~4.3.15~~ — On completion of construction of all approved crossovers, the City will assume responsibility for maintenance and any repairs due to catastrophic damage of all stormwater management infrastructure and the owner will be responsible for maintaining all surface treatments.

5.4. CROSSOVERS

~~4.1.1 4.1 General Conditions~~

~~4.1 The following general conditions apply to this Policy:~~

~~4.1 4.3.1 This policy only applies to local government gazetted roads.~~

~~4.1 4.3.2 Crossovers for properties that abut a State Government Road require Main Roads WA approval for crossover location, turning movement requirements, width and site distance. Construction of the crossover/drainage requirements and verge reinstatement are to be in accordance with the City's Vehicle Crossover Specification and must be approved by the City.~~

~~4.1 4.3.3 The approval of crossover construction is subject to the submission of an Application for Vehicle Crossover form and inspection processes, prior to commencing construction.~~

~~4.1 4.3.4 The property owner is responsible for contacting Dial Before You Dig (1100) and other service and utility providers prior to commencing construction to ensure that underground services and infrastructure are not damaged and correct clearances are maintained.~~

~~4.1 4.3.5 Vehicle crossovers shall be constructed under the supervision and to the satisfaction of the City's officers. Contractors/owners are responsible for notifying the City prior to any preparatory or construction works to ensure that the correct inspections are conducted.~~

~~4.1 4.3.6 The contractor/owner is responsible for all traffic and pedestrian management during the crossover construction, in accordance with AS1742.3 2009 Code of Practice for Traffic Management at Road Works.~~

~~4.1 4.3.7 The contractor shall maintain public liability insurance to the value of five million dollars (\$5,000,000) during the crossover construction.~~

~~4.1 4.3.8 The contractor/owner is responsible for repairs to any damaged infrastructure occurring during the crossover construction.~~

~~4.1 4.3.9 The contractor/owner is responsible for reinstatement and clean up of the verge immediately after completion of construction.~~

~~4.1 4.3.10 The City reserves the right to remove a crossover for the purpose of carrying out works. Reinstatement of an approved crossover shall be carried out by the City in consultation with the property owner.~~

~~4.1 4.3.11 The owner accepts responsibility for removal and reinstatement of crossovers if required by public utility providers.~~

~~4.1 4.3.12 A crossover subsidy will only apply to the first crossover installed at the property.~~

~~4.1 4.3.13 If a second crossover is required, the contractor/owner will be required to submit a Crossover Application Form and comply with all inspection processes, prior to commencing construction.~~

~~4.1 4.3.14 Redundant crossovers, due to redevelopment of a site, are to be removed. Replacement of kerb, backfilling and verge area to be reinstated at the owner's/developer's expense.~~

~~4.3.15 On completion of construction of all approved crossovers the City will assume responsibility for maintenance and any repairs due to catastrophic damage of all stormwater management infrastructure and the owner will be responsible for maintaining all surface treatments.~~

4.1 4.5.4.1 Crossover Specifications

A vehicle crossover must be designed and constructed in accordance with the City's *Vehicle Crossover Specification* and suited to the development type and vehicle usage requirements.

All new crossovers shall be constructed in accordance with the standard drawings and specifications provided by the City, unless approval is granted otherwise.

Crossovers over an open drain shall require the installation of culvert/pipes, rock pitching, headwalls or any other element relating to stormwater management necessary to maintain a steady flow through the drain. (refer Section 3.6) This must be designed in accordance with drainage guidelines contained within the City's *Vehicle Crossover Specification*.

4.2 4.5 Crossover Maintenance

The property owner shall be responsible for the maintenance of the crossover to ensure that it remains in a safe and trafficable condition. The City may request the owner to undertake repairs to the crossover at the owner's expense.

4.3 4.6 Crossover Subsidy

In accordance with the *Local Government (Uniform Local Provisions) Regulations 1996* (Sch. 9.1, c17):

"The local government is obliged to bear 50% of the cost, as estimated by the local government, of a standard crossing, but otherwise the local government is not obliged to bear, nor prevented from bearing, any of the cost."

The following conditions apply in relation to eligibility of a crossover for a subsidy:

~~4.3.1 4.6.1~~ Only the first crossover for a property is eligible for a subsidy

~~4.3.2 4.6.2~~ The subsidy shall apply to industrial, commercial and grouped dwellings as well as single residential. In the case of strata titles, a subsidy shall apply to each individual crossover up to the number of dwellings.

~~4.3.3 4.6.3~~ The subsidy must be claimed within six months from the date of completion.

~~4.3.4 4.6.4~~ Prior to crossover preparation or concrete pour, the applicant must:

- ~~_____ a)~~ Submit an Application for Vehicle Crossover form; ~~and~~
- ~~_____ b)~~ Carry out inspections with the City's officers.

~~4.3.5~~ Should Applicants pour concrete or construct the crossover prior to complying with items a) and b) above their right to claim a subsidy will be void.

~~4.3.6 4.6.5~~ The subsidy application shall be submitted with itemised evidence to support the cost of construction. The cost of implementing stormwater management measures, ~~as referred in Section 3.4,~~ is not eligible for subsidy.

The City of Karratha shall subsidise 50% of the crossover cost based on the dimensions of a standard crossover (as identified in Clause 2 – Definitions) and subject to the crossover complying with the City's *Vehicle Crossover Specification*.

5. REAR ACCESS DRIVEWAYS

5. _____

5.1 ~~General~~ Special Conditions

5.2 _____

The following general conditions for rear access driveways apply to this Policy:

~~5.1.1~~ ~~5.1.1~~ This policy only applies to local government gazetted roads.

~~5.1.2~~ ~~5.1.2~~ Rear access driveways for properties that abut a State Government Road require Main Roads WA approval for rear access driveway location, turning movement requirements, width and site distance. _____ Construction of the rear access driveway/drainage requirements and verge reinstatement are to be in accordance with the City's *Rear Access Driveway Specification* and must be approved by the City.

~~5.1.3~~ ~~5.1.3~~ The approval of Rear Access Way construction is subject to the submission of an Application for Vehicle Crossover form and inspection processes, prior to commencing construction. The approval of a rear access driveway construction is subject to the submission of an Application for Vehicle Crossover form and inspection processes, prior to commencing construction. The applicant shall contact the Technical Services Department ~~City of Karratha Technical Services Department to confirm requirements in regards to pipe size/need. Each case will be assessed individually and all construction to the satisfaction of Technical Services Department.~~

~~5.1.4~~ ~~5.1.4~~ The property owner is responsible for contacting the City of Karratha Technical Services Department to confirm access requirements in regards to pipe size/need specifications and arrange site visit. Each case will be assessed individually and all construction to the satisfaction of Technical Services Department.

~~Dial Before You Dig (1100) and other service and utility providers prior to commencing construction to ensure that underground services and infrastructure are not damaged and correct clearances are maintained.~~

~~5.1.5~~ Rear Access Driveways shall be constructed under the supervision and to the satisfaction of the City's officers. Contractors/owners are responsible for notifying the City prior to any preparatory or construction works to ensure that the correct inspections are conducted.

~~5.1.6~~ The contractor/owner is responsible for all traffic and pedestrian management during the rear access driveway construction, in accordance with AS1742.3 2009 Code of Practice for Traffic Management at Road Works.

~~5.1.7~~ The contractor shall maintain public liability insurance to the value of five million dollars (\$5,000,000) during the rear access driveway construction.

~~5.1.8~~ The contractor/owner is responsible for repairs to any damaged infrastructure occurring during the rear access driveway construction.

~~5.1.9~~ The contractor/owner is responsible for reinstatement and clean up of the verge immediately after completion of construction.

~~5.1.10~~ The City reserves the right to remove a rear access driveway for the purpose of carrying out works. Reinstatement of an approved rear access driveway shall be carried out by the City in consultation with the property owner.

~~5.1.11~~ The owner accepts responsibility for removal and reinstatement of rear access driveways if required by public utility providers.

~~5.1.12~~ Redundant rear access driveways, due to redevelopment of a site, are to be removed. Replacement of kerb, backfilling and verge area to be reinstated at the owner's/developer's expense.

~~5.1.13~~ On completion of construction of all approved rear access driveways the Owner will assume responsibility for maintenance and any repairs due to catastrophic damage of all stormwater management infrastructure and the owner will be responsible for maintaining all surface treatments.

~~5.1.14~~ Rear access driveways will be considered a secondary, alternative access and are therefore not eligible for the crossover subsidy

5.35.2 Rear Access Driveway Specifications

A Rear Access Driveway must be designed and constructed in accordance with the City's *Rear Access Driveways Specifications* and suited to the development type and vehicle usage requirements.

All new Rear Access Driveways shall be constructed in accordance with the standard drawings and specifications provided by the City, unless approval is granted otherwise.

Rear Access Driveways over an open drain, with batter greater than 1:6, shall require the installation of culvert/pipes, rock pitching, headwalls or any other element relating to stormwater management necessary to maintain a steady flow through the drain. This must be designed in accordance with drainage guidelines contained within the City's *Rear Access Driveway Specifications*.

5.45.3 Rear Access Driveway Maintenance

The property owner shall be responsible for the maintenance of the Rear Access Driveway to ensure that it remains in a safe and trafficable condition. The City may request the owner to undertake repairs to the rear access driveway at the owner's expense.

On completion of construction of all approved rear access driveways the Owner will assume responsibility for maintenance and any repairs due to catastrophic damage of all stormwater management infrastructure and the owner will be responsible for maintaining all surface treatments.

6.0 Rear Access Driveway Construction Options

The following is a list of rear access construction/surface options for consideration that can be utilised as application models and presented to Council for consideration. Upon application the City of Karratha Technical Services Team will assist in finding confirming a suitable rear access driveway option that satisfies the standard construction standards and requirements to maintain effective water flow.

Surface Treatment

Minimum: Gravel 100mm Road base	100mm compacted road base and 3m concrete apron
Optional Surface treatments:	
Concrete (as per City of Karratha / AS standard)	Excavation, 75mm base compacted. 100mm concrete and reo
2 Coat Bitumen Seal	2 coat bitumen seal Structural concrete kerb edging (optional)
Trafficable Brick Paving with concrete haunching	20m x 3m drive way with pavers

Culvert Options

Culvert: Concrete	Minimum pipe size to be 450mm. Size to be determined on application based on drainage flows required at access location.
Culvert: Plastream	Minimum pipe size to be 450mm. Size to be determined on application based on drainage flows required at access location.

Other

As approved by City technical Services Department

45.6. CONSEQUENCES

This policy represents the formal policy and expected standards of the Council. Appropriate approvals need to be obtained prior to any deviation from the policy. Elected Members and Employees are reminded of their obligations under the Council's Code of Conduct to give full effect to the lawful policies, decisions and practices of the Council.

47.7. ROLES AND RESPONSIBILITIES

The persons and groups that this policy is designed to be applied to are land developers and property owners.

48.8. REFERENCES TO RELATED DOCUMENTS

- *Local Government Act 1995,*
- *Local Government (Uniform Local Provisions) Regulations 1996*
- *City of Karratha Vehicle Crossover Specification and Drawings*
- *[City of Karratha Rea Access Way Specification and drawings](#)*

Policy Number:	TE.06
Previous Policy Number:	N/A
Resolution Numbers:	153724 - Feb 2017
Last Review:	July 2019 February 2017
Next Review:	July February 2022-2019
Responsible Officer:	Technical Services Coordinator

This Policy takes effect from the date of adoption by Council and shall remain valid until it is amended or deleted.